

NEOPRENE OR URETHANE SURFACE

PHONE: 516.328.3300 • FAX: 516.326.8827 • WWW.SDP-SI.COM

> MATERIAL:

Roller - Neoprene or Urethane 60 Durometer
Ground Outside Diameter


Sleeve - Aluminum

Bearing - Sintered Bronze




Fig. 1


Fig. 2




**Fig. 1
With Chamfer**



**NEOPRENE OR URETHANE
VULCANIZED TO SLEEVE**



**Fig. 2
Without Chamfer**



**URETHANE
VULCANIZED TO SLEEVE**

INCH COMPONENT

Catalog Number				O.D.	B Bore +.0015 -.0000	E Face Width ± .010	C Dia.	G Dia.	D	F
Neoprene**	Fig.	Urethane Δ	Fig.							
—	1	A 7Z 5-UR0512	2	1/2	1/8	23/32	1/4	11/32	1/32	1/32
A 7Z 5-IR0625		A 7Z 5-UR0625		43/64	1/4	1/4	3/8	1/2	—	—
—		A 7Z 5-UR0718	3/4	3/16	1/2	7/16			1/32	—
A 7Z 5-IR0721		A 7Z 5-UR0721	—	7/32			—	—	—	—
—		A 7Z 5-UR0825	1	13/16	1/4	31/64	3/8	11/16	1/64	1/64
—		A 7Z 5-UR0925		59/64					—	—
—		A 7Z 5-UR1125	2	1-1/8	1/4	7/16	3/8	1/2	1/32	—
—		A 7Z 5-UR1125W		—					11/16	—
*A 7Z 5-IR1937	—	*A 7Z 5-UR1937	—	1.988	—	.687	—	1-3/8	—	—

* Supplied less bearing.

ΔUrethane Idler Rollers will be supplied with chamfer until present stock is depleted.

After depletion, they will be sold without chamfer except for catalog number **A 7Z 5-UR0825**.

**To be discontinued when present stock is depleted.

1

R

T

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16